

## **AMENDMENTS TO THE CLAIMS**

The following listing of claims will replace all prior versions and listings of claims in the application.

### **LISTING OF CLAIMS**

1. (Previously Presented) An acetabular prosthetic comprising:  
a bone engagement surface;  
a first inner integral generally spherical polished concave bearing surface configured to directly engage an articulating surface of a femoral component; and  
a locking mechanism configured to couple a second prosthetic implant having a second spherical concave bearing surface, the second spherical concave bearing surface is configured to substantially surround a head of the femoral component.
2. (Original) The acetabular prosthetic according to claim 1 wherein said second prosthetic is selected from a group of a constraining ring, a slotted constraining ring, a bearing insert, and a bearing insert having an integral constraining ring and combinations thereof.
3. (Cancelled)
4. (Original) The acetabular prosthetic according to claim 1 further comprising a peripheral surface, which defines said locking mechanism, and wherein

said peripheral surface defines at least one aperture configured to accept a coupling fastener.

5. (Original) The acetabular prosthetic according to claim 1 wherein said second prosthetic implant comprises a polymer bearing surface.

6. (Original) The acetabular prosthetic according the claim 5 wherein said second prosthetic is a bearing insert.

7. (Original) The acetabular prosthetic according to claim 6 wherein said bearing insert comprises an integral constraining ring.

8. (Previously Presented) The acetabular prosthetic according to claim 7 wherein said bearing insert defines a bearing insert coupling groove configured to accept a locking ring.

9. (Original) The acetabular prosthetic according to claim 1 wherein said second prosthetic is a constraining ring.

10. (Original) The acetabular prosthetic according to claim 9 wherein said constraining ring includes a hemi-spherical bearing surface.

11. (Original) The acetabular prosthetic according to claim 9 wherein said constraining ring defines a constraining ring groove configured to accept a locking ring to couple said constraining ring to said first prosthetic.

12. (Original) The acetabular prosthetic according to claim 9 wherein said constraining ring defines a locking flange, said locking flange being configured to mate with said locking mechanism.

13. (Original) The acetabular prosthetic according to claim 9 wherein said constraining ring comprises a metal reinforcement ring.

14. (Original) An acetabular prosthetic according to claim 9 wherein said constraining ring comprises a restraining lip.

15. (Original) The acetabular prosthetic according to claim 9 wherein the constraining ring comprises a plurality of restraining lips.

16. (Original) The acetabular prosthetic according to claim 9 wherein the constraining ring comprises an exterior surface which defines a reinforcement accepting groove, said reinforcement accepting groove being configured to retain a reinforcement ring.

17. (Original) The acetabular prosthetic according to claim 9 wherein the constraining ring comprises an integrally molded reinforcement structure.

18. (Original) The acetabular prosthetic according to claim 17 wherein the reinforcement structure has a C-shaped cross-section.

19. (Currently Amended) The acetabular prosthetic according to claim 17 wherein the reinforcement structure is a bearing insert.

20. (Original) The acetabular prosthetic according to claim 9 wherein the constraining ring comprises a coupling plate having a plurality of elastically deformable coupling flanges which are configured to couple to the locking mechanism.

21. (Original) The acetabular prosthetic according to claim 1 wherein said first and second bearing surfaces define a generally capsule shaped cavity, said generally capsule shaped cavity is configured to rotatably accept a head of a femoral prosthetic and allow a translation of the head along a predetermined axis.

22. (Currently Amended) A kit of prosthetic components comprising:  
a femoral prosthetic having a metal articulating surface;  
an acetabular prosthetic defining an integral polished spherical bearing surface configured to directly interface with the metal articulating surface, and a locking mechanism configured to accept a second prosthetic device; and

at least one second prosthetic device having a partially spherical bearing surface, the partially spherical bearing surface is configured to ~~substantially~~ surround a portion of the head of a femoral component.

23. (Original) The kit according to claim 22 wherein said second prosthetic device is selected from a group consisting of a constraining ring, a bearing insert, a bearing having an integral constraining ring, and combinations thereof.

24. (Original) The kit according to claim 22 further comprising a plurality of femoral prosthetic components.

25. (Original) The kit according to claim 22 wherein said second prosthetic device is a constraining ring defining a constraining ring bearing surface and a constraining ring locking mechanism configured to fixably couple said constraining ring to said acetabular prosthetic.

26. (Original) The kit according to claim 22 wherein the second prosthetic device is a polymer bearing insert which defines an interior bearing surface and a bearing insert locking mechanism, wherein said bearing insert locking mechanism is configured to lock said polymer bearing insert to said acetabular prosthetic.

27. (Previously Presented) A method for implanting a medical device comprising:

implanting a first prosthetic having an integral polished internal bearing surface configured to directly interface with a metallic femoral bearing and a locking mechanism which is configured to fixably accept a second prosthetic having a second bearing surface which substantially surrounds a head portion of a femoral component, to a prepared joint; and

inserting a femoral prosthetic within the integral internal bearing surface of the first prosthetic.

28. (Original) The method according to claim 27 further comprising coupling a second prosthetic device to the locking mechanism after the first prosthetic device has been implanted in the prepared joint.

29. (Original) The method according to claim 27 further comprising coupling a polymer bearing insert to said locking mechanism.

30. (Original) The method according to claim 27 further comprising coupling a constraining ring to said locking mechanism.

31. (Original) The method according to claim 28 further comprising coupling a polymer bearing insert having an integral constraining ring to the locking mechanism.

32. (Original) The method according to claim 27 further comprising:  
removing the femoral prosthesis from said first prosthetic;  
coupling said second prosthetic to said first prosthetic; and  
inserting the femoral prosthesis into said first and second prosthetics.

33. (Previously Presented) A method for implanting a medical device comprising:

implanting a first prosthetic having an integral internal bearing surface and a locking mechanism which is configured to fixably accept a second prosthetic having a second bearing surface which substantially surrounds a head portion of a femoral component, to a prepared joint;

inserting a femoral prosthetic within the integral internal bearing surface of the first prosthetic;

removing the femoral prosthesis from said first prosthetic;

coupling said second prosthetic to said first prosthetic; and

inserting the femoral prosthesis into said first and second prosthetics, wherein said second prosthesis is disposed about said femoral implant prior to its coupling to said first prosthesis.

34. (Previously Presented) An acetabular prosthetic implant comprising:

a first member having a bone engagement surface and an integral generally spherical polished first bearing surface configured to interface with an

articulate surface of a femoral prosthetic, said first member defining a locking mechanism configured to be coupled to a second prosthetic member; and

a second prosthetic member, coupled to said locking mechanism, said second member defining a second semi-spherical bearing surface, said first and second bearing surfaces defining a generally capsule shaped cavity; and wherein said generally capsule shaped cavity is configured to rotatably accept a head of a femoral prosthetic and allow the translation of the head along a predetermined axis.

35. (Original) The acetabular prosthetic according to claim 34 wherein said integral first bearing surface is hemispherical.

36. (Original) The acetabular prosthetic according to claim 34 wherein one of said first and second prosthetic members further defines a generally cylindrical inner bearing surface.

37. (Original) The acetabular prosthetic according to claim 36 wherein said generally cylindrical inner bearing surface has a length of about 1 to about 4 mm.

38-43. (Cancelled)

44. (New) The acetabular prosthetic according to claim 1 further comprising a peripheral surface between the bone engaging surface and the concave bearing surface, and wherein said locking mechanism is a locking flange disposed

above a portion of peripheral surface and defining a locking groove between the locking flange and the peripheral surface, said locking flange further defining a plurality of alignment notches.

45. (New) The acetabular prosthetic according to claim 22 wherein the acetabular prosthetic defines a peripheral surface adjacent to the first bearing surface, said locking mechanism is a locking flange defining a plurality of alignment notches, and defining a locking groove between the locking flange and the peripheral surface.

46. (New) The acetabular prosthetic according to claim 34 wherein the acetabular prosthetic defines a peripheral surface adjacent to the first bearing surface, said locking mechanism defines a locking groove and a plurality of alignment notches.

47. (New) The acetabular prosthetic according to claim 1 wherein substantially all of the inner integral surface is a polished concave bearing surface.